Natural gas safety and you

Smell gas?

Look for blowing dirt, discolored vegetation or continued bubbling in standing water.

Listen for a hissing or roaring noise of natural gas escaping near an appliance or line.

Smell for the distinctive, rotten-egg odor associated with natural gas. Natural gas is colorless and odorless, so we add a chemical odorant called mercaptan for easy detection. This odorant has a distinctive "rotten egg" type odor. You should act any time you detect even a small amount of this odor in the air.







Do not try to identify the source or to stop the leak yourself.

Leave the area immediately and move a safe distance away from the potential leak, while avoiding any action that may cause sparks.

Avoid using any sources of ignition, such as cell phones, cigarettes, matches, flashlights, electronic devices, motorized vehicles, light switches or landlines, as natural gas can ignite from a spark or open flame, possibly causing a fire or explosion. Natural gas is non-toxic, lighter than air and displaces oxygen. In severe cases, if not used properly, natural gas can also lead to asphyxiation.

Call Atlanta Gas Light at **877.427.4321** or **911** once you are out of the area of the suspected leak and in a safe place. Stay away until Atlanta Gas Light or emergency personnel indicate it is safe to return.

Note: Be aware that some individuals may not be able to detect the odorant because they have a diminished sense of smell, olfactory fatigue or because the odor is being masked by other odors in the area. Certain conditions may cause the odorant to diminish so that it is not detectable. Some gas lines, due to their unique function, may not have odor at all.

Even though natural gas pipeline incidents are uncommon, you can help prevent emergencies by knowing the signs of a potential problem. Anytime you suspect a leak, leave the area immediately and call us at 877.427.4321.

Para solicitar una copia de esta información en español, llame al visite atlantagaslight.com/safetyspanish.



Plan ahead to stay safe

Planning a home improvement project? Planting a tree? Installing a fence or deck? **WAIT!** With any digging on your property, here's what you need to know first:



Excavation work, including digging or plowing around a home or business, is the most common cause of natural gas emergencies. Before digging around your property, state law requires you call **811**, a nationwide, toll-free number, to have your utility lines professionally marked. After calling, you must wait the required amount of time before digging, so underground utility lines can be located and marked – free of charge – before you begin your project.

Water heater safety

The U.S. Consumer Product Safety Commission urges all users to lower their water heaters to 120 degrees Fahrenheit.

A thermostat setting of 120 degrees Fahrenheit (49 degrees Celsius) may be necessary for residential water heaters to reduce or eliminate the risk of most tap water scald injuries. Consumers should consider lowering the thermostat to the lowest settings that will satisfy hot water needs for all clothing and dish washing machines.

Never take hot water temperature for granted. Always hand test before using, especially when bathing children and infants.

Gas piping

Atlanta Gas Light is responsible for maintaining the gas lines that deliver natural gas to the meter at your home or business. You are responsible for maintaining the gas lines from the meter to the natural gas-burning appliances throughout your home, business and property – indoors and outdoors, above and below ground. Don't forget that you may have gas lines extending to yard lights, grills, pool heaters and garage or workshop heaters.

Natural disasters

Should your property be affected by a natural disaster such as a flood, tornado or hurricane, be aware that appliance connectors and gas piping may be impacted. If a leak is suspected:

- Leave the building immediately and have others also exit immediately.
- Do not light a match, operate natural gas appliances, use a phone or turn an electrical switch on or off. Keep everyone away from the area of the odor. Do not start a car. Go to a nearby phone away from the smell and call Atlanta Gas Light at 877.427.4321 or 911.

It is recommended that any gas appliances that have been submerged in water be replaced.

Appliance connectors

Appliance connectors are corrugated metal tubes used to connect gas appliances to fuel gas supply pipes in your home or business. Some older brass connectors – that have not been made for more than 20 years, but that are still found in older homes and buildings – have a potential flaw in how the tubing is joined to end pieces. Over time, the end pieces can separate from the tubing and may cause a serious leak, explosion or fire.

Although not all uncoated connectors have this potential flaw, it is difficult to tell which ones do. Therefore, any uncoated brass connector should be replaced immediately by a certified contractor.

Be sure to follow these appliance connector guidelines:

- Make sure that connectors are installed where no one will step, sit, lean or place a heavy object on them.
- · Never have a connector installed through a wall, floor or ceiling.
- · An appliance connector should not be more than six feet long.
- Each appliance should have a shut-off valve installed on the house piping before the connector.
- A new connector should be installed by a certified contractor every time an appliance is replaced.

Visit **atlantagaslight.com/safety** for additional natural gas safety information.

Excess flow valves

An excess flow valve is a supplemental mechanical device installed inside a natural gas distribution service line.

To learn more, visit atlantagaslight.com/efv.

Pipeline integrity management is a process for assessing and mitigating pipeline risks to reduce both the likelihood and consequences of incidents. We have a comprehensive plan that fully addresses these processes, especially for locations deemed high-consequence areas. To learn more, visit atlantagaslight.com/integritymanagementplan.